

## WOMENS TENCATE TECASAFE® PLUS 700 TAPED 2T HI VIS FR VENTED SHIRT LS

### BL8082T

#### Features

- Inherent Flame resistant fabric - Tencate Tecasafe® Plus
- Sto-nor 9801 FR Reflective taped 'Hoop' pattern around body and sleeves
- Two piece structured contrast collar
- Two way radio loop or gas monitor loop on both shoulders
- Action back panel ventilation with two openings and underarm ventilation
- Twin chest pockets with plastic press snap closure. Left pocket with pen division
- Full gusset sleeve cuff with plastic snap closure

#### Fabric

- TenCate Tecasafe® Plus 700 FR Modacrylic/Lyocell/Aramid 238gsm
- Tecasafe® Plus Open Mesh

#### Arc Thermal Protection Value

- ATPV 9

#### Personal Protective Equipment Category


- PPE 2

#### Size

- 8 - 24



Yellow/Navy (TT01)    Orange/Navy (TT02)



TENCATE  
Tecasafe® Plus

BL8082T

[www.bisleyworkwear.com.au](http://www.bisleyworkwear.com.au)

## TECHNICAL FAQ's

**What is the centre back body length (CB neck to hem)?**

**8:** 71cm, **10:** 72cm, **12:** 73cm, **14:** 74cm,  
**16:** 75cm, **18:** 76cm, **20:** 77cm,  
**22:** 78cm, **24:** 79cm,

**What is UPF rating of the fabric on this shirt?**

- UPF 50+

## SIMILAR PRODUCTS



**BL8097T**  
WOMENS TENCATE TECASAFE®  
PLUS 580 TAPED HI VIS LW FR  
VENTED SHIRT LS



**BL8098T**  
WOMENS TENCATE TECASAFE®  
PLUS 580 TAPED 2T HI VIS LW FR  
VENTED SHIRT LS



**BLC8075T**  
WOMENS TENCATE TECASAFE®  
PLUS 580 TAPED 2T HI VIS CLOSE  
FRONT FR SHIRT LS

## AUSTRALIAN & INTERNATIONAL STANDARDS

### ALL BISLEY GARMENTS COMPLY WITH CARE LABELLING STANDARDS:

- **AS/NZS 2621:1998:** Textiles - Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957
- **AS/NZS 2392:1999:** Textiles - Labelling of Clothing, Household Textiles and Furnishings
- **AS/NZS 1957:1998:** Textiles - Care Labelling
- **AS/NZS 2622:1996:** Textile Products - Fibre Content Labelling

### Australian/ New Zealand Standards

#### AS/NZS 4602.1:2011: HI VISIBILITY SAFETY GARMENTS. GARMENTS FOR HIGH RISK APPLICATION

- *This garment has a minimum of 0.2sqm of hi visibility fabric on the front and back and retro-reflective taping configuration - hoop pattern to meet day & night standard*

#### AS/NZS 1906.4:2010: HI VISIBILITY MATERIAL FOR SAFETY GARMENTS

- *This garment meets the fluorescent capabilities and the chromaticity reading to ensure that the bright colours are within the required colour range. Retro-reflective tape on this garment also meets the higher retro-reflective performance required.*

#### AS/NZS 4399:1996: SUN PROTECTIVE CLOTHING - EVALUATION AND CLASSIFICATION

- *This garment has a sun protection rating of UPF 50+ all colours*

### International Standards

#### NFPA70E: ELECTRICAL SAFETY IN THE WORKPLACE

- ASTM F1959 / F1959M - 14 Arc Rating results of ATPV 9.0 cal/cm<sup>2</sup> PPE 2
- ASTM F1506\_15

#### NFPA2112: FLAME RESISTANT GARMENTS FOR PROTECTION OF INDUSTRIAL PERSONNEL AGAINST FLASH FIRE

- ASTM F1930:2015 Flash Fire Exposure (% body burn [2 cal/cm / sec] @ 3 sec) \_ PASS
- ASTM D6413 / D6413M - 15 Vertical Flame Test

#### ISO 11612: PROTECTIVE CLOTHING AGAINST HEAT AND FLAME

- ISO 15025:2000 - Flame Spread [Face and Edge ignition]\_ No hole formation.No Molten or flaming debris. No after flame.

### ALL STYLES

### WOMENS

Size	8	10	12	14	16	18	20	22	24
To fit bust size (cm)	85	90	95	100	105	110	115	120	125
To fit natural waist size (cm)	65	70	75	80	85	90	95	100	105
To fit lower waist size (cm)	72	77	82	87	92	97	102	107	112
To fit hip size (cm)	92	97	102	107	112	117	122	127	132
In-leg length (cm)	80	80	82	82	84	84	86	86	86

**BL8082T**

[www.bisleyworkwear.com.au](http://www.bisleyworkwear.com.au)