

## TENCATE TECASAFE® PLUS 580 TAPED LIGHTWEIGHT FR PANT

### BP8190T

#### Features

- Inherent Flame resistant fabric - Tecasafe® Plus
- Sto-nor 9801 FR Reflective taped around upper legs
- Straight waistband
- Front angled pockets with reinforced opening
- YKK branded zip front fly
- Single back patch pocket with plastic press stud flap closure
- YKK branded zip front fly
- Single back patch pocket with plastic press stud flap closure
- Wide belt loops

#### Fabric

- TenCate Tecasafe® Plus 580A FR Modacrylic/Lyocell/Aramid 197gsm

#### Arc Thermal Protection Value

- ATPV 5.7

#### Personal Protective Equipment Category

- PPE 1

#### Size

- Reg: 77R-112R
- Stout: 87S-132S



Navy  
**(BPCT)**



7 wide belt loops

Back RHS patch pocket with plastic press stud flap closure

Twin needle stitching on front and back rise for extra seam reinforcement



Straight waistband

Front angled pockets

YKK branded fly zipper

Reinforced internal front rise seam

FR Retroreflective tape around upper legs

Twin needle stitching along side seam



TENCATE Tecasafe® Plus

**BP8190T**

[www.bisleyworkwear.com.au](http://www.bisleyworkwear.com.au)

## TECHNICAL FAQ's

**What is the inleg length on Regular (crotch to finish hem)?**

- **77:** 80cm, **82:** 82cm, **87:** 82cm, **92:** 84cm, **97:** 84cm, **102:** 86cm, **107:** 86cm, **112:** 88cm

**What is the inleg length on Stout (crotch to finish hem)?**

- **87:** 78cm, **92:** 80cm, **97:** 80cm, **102:** 82cm, **107:** 82cm, **112:** 84cm, **117:** 84cm, **122:** 84cm, **127:** 84cm, **132:** 84cm

## SIMILAR PRODUCTS



**BP8090T**  
TENCATE TECASAFE® PLUS 700 TAPED FR PANT



**BPC8092T**  
TENCATE TECASAFE® PLUS 700 TAPED ENGINEERED FR VENTED CARGO PANT



**BP8093T**  
TENCATE TTECASAFE® PLUS 700 TAPED FR PANT WITH DOUBLE LAYER KNEE

## AUSTRALIAN & INTERNATIONAL STANDARDS

### ALL BISLEY GARMENTS COMPLY WITH CARE LABELLING STANDARDS:

- **AS/NZS 2621:1998:** Textiles - Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957
- **AS/NZS 2392:1999:** Textiles - Labelling of Clothing, Household Textiles and Furnishings
- **AS/NZS 1957:1998:** Textiles - Care Labelling

### Australian/ New Zealand Standards

### AS/NZS 4399:1996: SUN PROTECTIVE CLOTHING - EVALUATION AND CLASSIFICATION

- *This garment has a sun protection rating of UPF 50+ for all colours*

### AS/NZS 1906.4:2010: HI VISIBILITY MATERIAL FOR SAFETY GARMENTS

- *Retro-reflective tape used on this garment meets the specific retro-reflective performance requirements under this standard for Class R material.*

### International Standards

### NFPA70E: ELECTRICAL SAFETY IN THE WORKPLACE

- ASTM F1959 / F1959M - 14 Arc Rating results of ATPV 5.7 cal/cm<sup>2</sup> PPE 1
- ASTM F1506\_15

### NFPA2112: FLAME RESISTANT GARMENTS FOR PROTECTION OF INDUSTRIAL PERSONNEL AGAINST FLASH FIRE

- ASTM F1930:2015 Flash Fire Exposure (% body burn [2 cal/cm / sec] @ 3 sec) \_ PASS
- ASTM D6413 / D6413M - 15 Vertical Flame Test

### ISO 11612: PROTECTIVE CLOTHING AGAINST HEAT AND FLAME

- ISO 15025:2000 - Flame Spread [Face and Edge ignition]\_ No hole formation. No Molten or flaming debris. No after flame.

### PANTS: Regular

### MENS

To fit waist size (cm)	<b>77</b>	<b>82</b>	<b>87</b>	<b>92</b>	<b>97</b>	<b>102</b>	<b>107</b>	<b>112</b>
To fit waist size (inches)	30	32	34	36	38	40	42	44
Inner leg length (cm)	80	82	82	84	84	86	86	88

### PANTS: Stout

### MENS

To fit waist size (cm)	<b>87</b>	<b>92</b>	<b>97</b>	<b>102</b>	<b>107</b>	<b>112</b>	<b>117</b>	<b>122</b>	<b>127</b>	<b>132</b>
To fit waist size (inches)	34	36	38	40	42	44	46	48	50	52
Inner leg length (cm)	78	80	80	82	82	84	84	84	84	84

**BP8190T**

[www.bisleyworkwear.com.au](http://www.bisleyworkwear.com.au)