

## TENCATE TECASAFE® PLUS 580 TAPED LIGHTWEIGHT FR CARGO PANT

### BPC8189T

#### Features

- Inherent Flame resistant fabric - Tencate Tecasafe® Plus
- Sto-nor 9801 FR Reflective tape around lower legs
- Front angled pockets with reinforced opening
- YKK branded zip front fly
- Straight waistband
- Front angled pockets with reinforced opening
- Cargo pockets with plastic press stud flap closure
- Single back patch pocket with plastic press stud flap closure
- Wide belt loops

#### Fabric

- TenCate Tecasafe® Plus 580A  
FR Modacrylic/Lyocell/Aramid  
197gsm

#### Arc Thermal Protection Value

- ATPV 7.1

#### Personal Protective Equipment Category

- PPE 1

#### Size

- Reg: 77R-112R
- Stout: 87S-132S



Navy  
(BPC)



TENCATE  
Tecasafe Plus

BPC8189T

[www.bisleyworkwear.com.au](http://www.bisleyworkwear.com.au)

## TECHNICAL FAQ's

### What is the inleg length on Regular (crotch to finish hem)?

- **77:** 80cm, **82:** 82cm, **87:** 82cm, **92:** 84cm, **97:** 84cm, **102:** 86cm, **107:** 86cm, **112:** 88cm

### What is the inleg length on Stout (crotch to finish hem)?

- **87:** 78cm, **92:** 80cm, **97:** 80cm, **102:** 82cm, **107:** 82cm, **112:** 84cm, **117:** 84cm, **122:** 84cm, **127:** 84cm, **132:** 84cm

## SIMILAR PRODUCTS



**BPC8092**

TENCATE TECASAFE® PLUS 700  
ENGINEERED FR VENTED  
CARGO PANT



**BP8090T**

TENCATE TECASAFE®  
PLUS 700 TAPED  
FR PANT



**BP8093T**

TENCATE TTECASAFE® PLUS  
700 TAPED FR PANT WITH  
DOUBLE LAYER KNEE

## AUSTRALIAN & INTERNATIONAL STANDARDS

### ALL BISLEY GARMENTS COMPLY WITH CARE LABELLING STANDARDS:

- **AS/NZS 2621:1998:** Textiles - Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957
- **AS/NZS 2392:1999:** Textiles - Labelling of Clothing, Household Textiles and Furnishings
- **AS/NZS 1957:1998:** Textiles - Care Labelling

### Australian/ New Zealand Standards

### AS/NZS 4399:1996: SUN PROTECTIVE CLOTHING - EVALUATION AND CLASSIFICATION

- *This garment has a sun protection rating of UPF 50+ for all colours*

### AS/NZS 1906.4:2010: HI VISIBILITY MATERIAL FOR SAFETY GARMENTS

- *Retro-reflective tape used on this garment meets the specific retro-reflective performance requirements under this standard for Class R material.*

### International Standards

### NFPA70E: ELECTRICAL SAFETY IN THE WORKPLACE

- ASTM F1959 / F1959M - 14 Arc Rating results of ATPV 10.0 cal/cm<sup>2</sup> PPE 2
- ASTM F1506\_15

### NFPA2112: FLAME RESISTANT GARMENTS FOR PROTECTION OF INDUSTRIAL PERSONNEL AGAINST FLASH FIRE

- ASTM F1930:2015 Flash Fire Exposure (% body burn [2 cal/cm / sec] @ 3 sec) \_ PASS
- ASTM D6413 / D6413M - 15 Vertical Flame Test

### ISO 11612: PROTECTIVE CLOTHING AGAINST HEAT AND FLAME

- ISO 15025:2000 - Flame Spread [Face and Edge ignition]\_ No hole formation. No Molten or flaming debris. No after flame.

### PANTS: Regular

### MENS

To fit waist size (cm)	<b>77</b>	<b>82</b>	<b>87</b>	<b>92</b>	<b>97</b>	<b>102</b>	<b>107</b>	<b>112</b>
To fit waist size (inches)	30	32	34	36	38	40	42	44
Inner leg length (cm)	80	82	82	84	84	86	86	88

### PANTS: Stout

### MENS

To fit waist size (cm)	<b>87</b>	<b>92</b>	<b>97</b>	<b>102</b>	<b>107</b>	<b>112</b>	<b>117</b>	<b>122</b>	<b>127</b>	<b>132</b>
To fit waist size (inches)	34	36	38	40	42	44	46	48	50	52
Inner leg length (cm)	78	80	80	82	82	84	84	84	84	84

**BPC8189T**

[www.bisleyworkwear.com.au](http://www.bisleyworkwear.com.au)