

## TENCATE TECASAFE® PLUS 700 TAPED 2T HI VIS FR VENTED SHIRT LS

### BS8082T

#### Features

- Inherent Flame resistant fabric -Tencate Tecasafe® Plus
- Sto-nor 9801 FR Reflective taped 'Hoop' pattern around body and sleeves
- Two piece structured contrast collar
- Two way radio loop or gas monitor loop on both shoulders
- Button down front closure
- Action back panel ventilation with two openings and underarm ventilation
- Twin chest pockets with plastic press snap closure. Left pocket with pen division
- Full gusset sleeve cuff with plastic snap closure

#### Fabric

- TenCate Tecasafe® Plus 700 FR Modacrylic/Lyocell/Aramid 238gsm
- Tecasafe® Plus Open Mesh

#### Arc Thermal Protection Value

- ATPV 9

#### Personal Protective Equipment Category


- PPE 2

#### Size

- S - 6XL



Yellow/Navy (TT01) Orange/Navy (TT02)



TENCATE  
Tecasafe® Plus

BS8082T

[www.bisleyworkwear.com.au](http://www.bisleyworkwear.com.au)

## TECHNICAL FAQ's

**What is the centre back body length (CB neck to hem)?**

**S:** 79cm, **M:** 81cm, **L:** 83cm, **XL:** 85cm,  
**2XL:** 87cm, **3XL:** 89cm, **4XL:** 92cm,  
**5XL:** 96cm, **6XL:** 100cm,

**What is UPF rating of the fabric on this shirt?**

- UPF 50+

## SIMILAR PRODUCTS



**BS8237T**

TENCATE TECASAFE® PLUS 480  
TAPED 2T HI VIS LIGHTWEIGHT FR  
VENTED SHIRT LS



**BS8098T**

TENCATE TECASAFE® PLUS 580  
TAPED 2T HI VIS LW FR  
VENTED SHIRT LS



**BSC8082T**

TENCATE TECASAFE® PLUS 700  
TAPE 2 TONE HI VIS FR CLOSED  
FRONT VENTED SHIRT LS

## AUSTRALIAN & INTERNATIONAL STANDARDS

### ALL BISLEY GARMENTS COMPLY WITH CARE LABELLING STANDARDS:

- **AS/NZS 2621:1998:** Textiles - Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957
- **AS/NZS 2392:1999:** Textiles - Labelling of Clothing, Household Textiles and Furnishings
- **AS/NZS 1957:1998:** Textiles - Care Labelling
- **AS/NZS 2622:1996:** Textile Products - Fibre Content Labelling

### Australian/ New Zealand Standards

#### AS/NZS 4602.1:2011: HI VISIBILITY SAFETY GARMENTS. GARMENTS FOR HIGH RISK APPLICATION

- *This garment has a minimum of 0.2sqm of hi visibility fabric on the front and back and retro-reflective taping configuration - hoop pattern to meet day & night standard*

#### AS/NZS 1906.4:2010: HI VISIBILITY MATERIAL FOR SAFETY GARMENTS

- *This garment meets the fluorescent capabilities and the chromaticity reading to ensure that the bright colours are within the required colour range. Retro-reflective tape on this garment also meets the higher retro-reflective performance required.*

#### AS/NZS 4399:1996: SUN PROTECTIVE CLOTHING - EVALUATION AND CLASSIFICATION

- *This garment has a sun protection rating of UPF 50+ for all colours*

### International Standards

#### NFPA70E: ELECTRICAL SAFETY IN THE WORKPLACE

- ASTM F1959 / F1959M - 14 Arc Rating results of ATPV 9.0 cal/cm<sup>2</sup> PPE 2
- ASTM F1506\_15

#### NFPA2112: FLAME RESISTANT GARMENTS FOR PROTECTION OF INDUSTRIAL PERSONNEL AGAINST FLASH FIRE

- ASTM F1930:2015 Flash Fire Exposure (% body burn [2 cal/cm / sec] @ 3 sec) \_ PASS
- ASTM D6413 / D6413M - 15 Vertical Flame Test

#### ISO 11612: PROTECTIVE CLOTHING AGAINST HEAT AND FLAME

- ISO 15025:2000 - Flame Spread [Face and Edge ignition]\_ No hole formation. No Molten or flaming debris. No after flame.

### SHIRTS

Size	S	M	L	XL	2XL	3XL	4XL	5XL	6XL
To fit neck size (cm)	37/38	39/40	41/42	43/44	46	48	50	52	54
To fit chest size (cm)	92	97	102	107	112	117	122	127	132
To fit chest size (inches)	36	38	40	42	44	46	48	50	52

### MENS

**BS8082T**

[www.bisleyworkwear.com.au](http://www.bisleyworkwear.com.au)