

TENCATE TECASAFE® PLUS 580 TAPED 2 TONE HI VIS LIGHT WEIGHT FR NON VENTED SHIRT LS

BS8198T

Features

- Inherent Flame resistant fabric Tencate Tecasafe® Plus
- Sto-nor 9801 FR Reflective taped 'Hoop' pattern around body and sleeves
- Two piece structured contrast collar
- Concealed press snap front closure
- Two way radio loop or gas monitor loop on both shoulders
- Twin chest pockets with plastic press snap flap closure. Left pocket with pen division
- Full gusset sleeve cuff with plastic snap closure

Fabric

 TenCate Tecasafe® Plus 580 FR Modacrylic/Lyocell/Aramid 197gsm

Arc Thermal Protection Value

• ATPV 6.5

Personal Protective Equipment Category

• PPE 1

Size

• S - 6XL



Yellow/Navy Orange/Navy (TT01) (TT02)

























TECHNICAL FAQ's

What is the sleeve length (sleeve head to cuff)?

S: 60cm, **M:** 61.5cm, **L:** 63cm, **XL:** 64.5cm, **2XL:** 66cm, **3XL:** 67.5cm, **4XL:** 69cm, **5XL:** 70.5m, **6XL:** 72cm

What is UPF rating of the fabric on this shirt?

• UPF 50+

SIMILAR PRODUCTS



BS8197T TENCATE TECASAFE® PLUS 580 TAPED HI VIS FR NON VENTED SHIRT LS



BS8237T TENCATE TECASAFE® PLUS 480 TAPED 2T HI VIS LIGHTWEIGHT FR VENTED SHIRT LS



BS8098T TENCATE TECASAFE® PLUS 580 TAPED 2T HI VIS LW FR VENTED SHIRT LS

AUSTRALIAN & INTERNATIONAL STANDARDS

ALL BISLEY GARMENTS COMPLY WITH Australian/ New Zealand Standards **CARE LABELLING STANDARDS:**

- AS/NZS 2621:1998: Textiles Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957
- AS/NZS 2392:1999: Textiles -Labelling of Clothing, Household Textiles and Furnishings
- AS/NZS 1957:1998: Textiles Care Labelling
- AS/NZS 2622:1996: Textile Products - Fibre Content Labelling

AS/NZS 4602.1:2011: HI VISIBILITY SAFETY GARMENTS. GARMENTS FOR **HIGH RISK APPLICATION**

 This garment has a minimum of 0.2sqm of hi visibility fabric on the front and back and retro-reflective taping configuration - hoop pattern to meet day & night standard

AS/NZS 1906.4:2010: HI VISIBILITY **MATERIAL FOR SAFETY GARMENTS**

• This garment meets the fluorescent capabilities and the chromaticity reading to ensure that the bright colours are within the required colour range. Retro-reflective tape on this garment also meets the higher retroreflective performance required.

AS/NZS 4399:1996: SUN PROTECTIVE **CLOTHING - EVALUATION AND CLASSIFICATION**

• This garment has a sun protection rating of UPF 50+ for all colours

International Standards

NFPA70E: ELECTRICAL SAFETY IN THE **WORKPLACE**

- ASTM F1959 / F1959M 14 Arc Rating results of ATPV 6.5 cal/cm² PPE 1
- ASTM F1506 15

NFPA2112: FLAME RESISTANT GARMENTS FOR PROTECTION OF INDUSTRIAL PERSONNEL AGAINST FLASH FIRE

- ASTM F1930:2015 Flash Fire Exposure (% body burn [2 cal/cm / sec] @ 3 sec) _ PASS
- ASTM D6413 / D6413M 15 Vertical Flame Test

ISO 11612: PROTECTIVE CLOTHING AGAINST HEAT AND FLAME

• ISO 15025:2000 - Flame Spread [Face and Edge ignition] No hole formation. No Molten, flaming debris. No after flame.

SHIRTS									
Size	S	M	L	XL	2XL	3XL	4XL	5XL	6XL
To fit neck size (cm)	37/38	39/40	41/42	43/44	46	48	50	52	54
To fit chest size (cm)	92	97	102	107	112	117	122	127	132
To fit chest size (inches)	36	38	40	42	44	46	48	50	52