

TENCATE TECASAFE® PLUS 580 TAPED 2T HI VIS CLOSED FRONT VENTED SHIRT WITH CONCEALED FRONT PLACKET

BSC8075T

Features

- Inherent Flame resistant fabric - Tencate Tecasafe® Plus
- Sto-nor 9801 FR Reflective taped 'Hoop' pattern around body and sleeves
- Closed front concealed placket with button closure
- Two piece structured contrast collar
- Two way radio loop or gas monitor loop on both shoulders
- Action back panel ventilation with two openings and underarm ventilation
- Twin chest pockets with plastic press snap closure. Left pocket with pen division
- Full gusset sleeve cuff with plastic snap closure

Fabric

- TenCate Tecasafe® Plus 580 FR Modacrylic/Lyocell/Aramid 197gsm
- Tecasafe® Plus Open Mesh

Arc Thermal Protection Value

- ATPV 6.5

Personal Protective Equipment Category

- PPE 1


Size

- S - 6XL



Yellow/Navy
(TT01)

Orange/Navy
(TT02)



TENCATE
Tecasafe® Plus

BSC8075T

www.bisleyworkwear.com.au

TECHNICAL FAQ's

SIMILAR PRODUCTS

What is the sleeve length (sleeve head to cuff)?

S: 60cm, **M:** 61.5cm, **L:** 63cm,
XL: 64.5cm, **2XL:** 66cm, **3XL:** 67.5cm,
4XL: 69cm, **5XL:** 70.5m, **6XL:** 72cm

What is UPF rating of the fabric on this shirt?

- UPF 50+



BS8237T

TENCATE TECASAFE® PLUS 480
 TAPED 2T HI VIS LIGHTWEIGHT FR
 VENTED SHIRT LS



BS8198T

TENCATE TECASAFE® PLUS 580
 TAPED 2T HI VIS FR
 NON VENTED SHIRT LS



BSC8082T

TENCATE TECASAFE® PLUS 700
 TAPE 2 TONE HI VIS FR CLOSED
 FRONT VENTED SHIRT LS

AUSTRALIAN & INTERNATIONAL STANDARDS

ALL BISLEY GARMENTS COMPLY WITH CARE LABELLING STANDARDS:

- **AS/NZS 2621:1998:** Textiles - Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957
- **AS/NZS 2392:1999:** Textiles - Labelling of Clothing, Household Textiles and Furnishings
- **AS/NZS 1957:1998:** Textiles - Care Labelling
- **AS/NZS 2622:1996:** Textile Products - Fibre Content Labelling

Australian/ New Zealand Standards

AS/NZS 4602.1:2011: HI VISIBILITY SAFETY GARMENTS. GARMENTS FOR HIGH RISK APPLICATION

- This garment has a minimum of 0.2sqm of hi visibility fabric on the front and back and retro-reflective taping configuration - hoop pattern to meet day & night standard

AS/NZS 1906.4:2010: HI VISIBILITY MATERIAL FOR SAFETY GARMENTS

- This garment meets the fluorescent capabilities and the chromaticity reading to ensure that the bright colours are within the required colour range. Retro-reflective tape on this garment also meets the higher retro-reflective performance required.

AS/NZS 4399:1996: SUN PROTECTIVE CLOTHING - EVALUATION AND CLASSIFICATION

- This garment has a sun protection rating of UPF 50+ all colours.

EN 614:2007: NATIONAL GUIDELINES FOR SELECTION, USE & MAINTENANCE OF PERSONAL PROTECTIVE EQUIPMENT FOR ELECTRICAL HAZARDS

- Designed to meet under these guidelines

International Standards

NFPA70E: ELECTRICAL SAFETY IN THE WORKPLACE

- ASTM F1959 / F1959M - 14 Arc Rating results of ATPV 6.5 cal/cm² PPE 1
- ASTM F1506_15

NFPA2112: FLAME RESISTANT GARMENTS FOR PROTECTION OF INDUSTRIAL PERSONNEL AGAINST FLASH FIRE

- ASTM F1930:2015 Flash Fire Exposure (% body burn [2 cal/cm / sec] @ 3 sec) _ PASS
- ASTM D6413 / D6413M - 15 Vertical Flame Test

ISO 11612: PROTECTIVE CLOTHING AGAINST HEAT AND FLAME

- ISO 15025:2000 - Flame Spread [Face and Edge ignition]_ No hole formation. No Molten or flaming debris. No after flame.

SHIRTS

MENS

Size	S	M	L	XL	2XL	3XL	4XL	5XL	6XL
To fit neck size (cm)	37/38	39/40	41/42	43/44	46	48	50	52	54
To fit chest size (cm)	92	97	102	107	112	117	122	127	132
To fit chest size (inches)	36	38	40	42	44	46	48	50	52

BSC8075T

www.bisleyworkwear.com.au